

PS1000

Features

Construction– Rugged steel with tread plate surface protects animals and handlers from accidental slips and falls. Adjustable foot pads allow scale to work effectively on uneven floors.

Overload Capacity– Capable of withstanding 150% capacity of weight without damaging the scale.

Easy Assembly– No installation costs or parts that require maintenance. Just place the scale on a hard surface and level by adjusting the foot pads. Connect the indicator and turn on the power.



Shown with optional indicator stand



Shown with optional indicator stand

Specifications

Capacity– 1,000 lbs x 0.5 lb (500 kg x 0.2 kg)

Power– Four (4) AAA batteries or 6 VDC, 500mA adapter, both included

Operating Temp– 41° F to 95° F (5° C to 35° C)

Battery Life– 20 hours

Display– Five 0.625" digits (17 mm) LCD display

Scale Dimensions–

Scale: 55.75" (L) x 20.25" (W) x 2.5" (H)

Shipping Carton: 57.5" (L) x 22" (W) x 4" (H)

Scale Weight– 60 pounds (27 kg)

Shipping Weight– 68 pounds (31 kg)



Indicator– 6.375" (L) x 3.125" (H) x 1.125" (W)

Serial Port– One full duplex RS232, with cable

Keyboard– Hold/Print, Units, Tare, On/Off/Zero

Unit– lb, kg, lb/oz

Option– Indicator stand

Stand - height 36"; weight 10 lbs

Stand base - 11.5" (L) x 11.5" (W) x .75 (H)

Certifications– Full FCC compliance, UL/CUL power adapter

